



DG Integration

Carl Lenox

September 14th, 2012

Safe Harbor Statement

This presentation contains forward-looking statements within the meaning of the Private Securities litigation Reform Act of 1995. Forward-looking statements are statements that do not represent historical facts and may be based on underlying assumptions. SunPower uses words and phrases such as “driving,” “within reach,” “predictable,” “will,” “pipeline,” “visibility,” “goal,” “projected,” “target schedule” and similar words and phrases to identify forward-looking statements in this presentation, including forward-looking statements regarding: (a) plans and expectations regarding future financial results, operating results, liquidity, cash flows, capital expenditure and business strategies, (b) management’s plans and objectives for future operations, (c) reaching the goal of mass market cost-effectiveness and competing with conventional energy sources, (d) forecasted demand growth in the solar industry, and projected bookings and pipelines, (e) utility project construction and timing, completion, ability to obtain financing, (f) growth in dealer partners, (g) product development, advantages of new products, and competitive positioning, (h) manufacturing plans and expected savings, and (i) the success and benefits of joint ventures, acquisitions and partnerships. Such forward-looking statements are based on information available to SunPower as of the date of this presentation and involve a number of risks and uncertainties, some beyond SunPower’s control, that could cause actual results to differ materially from those anticipated by these forward-looking statements, including risks and uncertainties such as (i) increasing supply and competition in the industry and lower ASPs, impact on gross margins, and any revaluation of inventory as a result of decreasing ASP or reduced demand; (ii) the impact of regulatory changes and the continuation of governmental and related economic incentives promoting the use of solar power, and the impact of such changes on revenues, financial results; (iii) ability to meet cost reduction plans and reduce operating expenses; (iv) ability to obtain and maintain an adequate supply of raw materials, components, and solar panels, as well as the price paid for such items and third parties’ willingness to renegotiate or cancel above market contracts; (v) general business and economic conditions, including seasonality of the solar industry, growth trends in the solar industry, and the challenges in becoming price competitive with conventional energy sources; (vi) ability to revise portfolio allocation geographically and across downstream channels to respond to regulatory changes; (vii) ability to increase or sustain growth rate; (viii) construction difficulties or potential delays, including obtaining land use rights, permits, license, other governmental approvals, and transmission access and upgrades, and any litigation relating thereto; (ix) timeline for revenue recognition and impact on operating results; (x) the significant investment required to construct power plants and the company’s ability to sell or otherwise monetize power plants, including the company’s success in completing the design, construction and maintenance of CVSR and the 711MW project for Southern California Edison; (xi) fluctuations and unpredictability in operating results; (xii) the availability of financing arrangements for the company’s projects and the company’s customers; (xiii) potential difficulties associated with operating the joint venture with AUO and ability to achieve the anticipated synergies with Tenesol; (xiv) success in achieving cost reduction, ability to remain competitive in product offering and obtain premium pricing; (xv) liquidity, substantial indebtedness, and ability to obtain additional financing and meet debt covenants; (xvi) manufacturing difficulties that could arise; (xvii) ability to achieve the expected benefits from relationship with Total; (xviii) the success of ongoing R&D efforts and the acceptance of new products and services, and ability to protect its IP; (xix) possible impairment or write-off of goodwill, intangible assets, long-lived assets and project assets; (xx) the success of residential lease program; (xxi) the assumptions and compliance with treasury grant guidance and timing and amount of cash grant; (xxii) the possible consolidation of AUO SunPower, and (xxiii) other risks described in SunPower’s Annual Report on Form 10-K for the year ended January 1, 2012 and Quarterly Report on Form 10-Q for the quarter end April 1, 2012 other filings with the Securities and Exchange Commission. These forward-looking statements should not be relied upon as representing SunPower’s views as of any subsequent date, and SunPower is under no obligation to, and expressly disclaims any responsibility to, update or alter its forward-looking statements, whether as a result of new information, future events or otherwise.

© 2012 SunPower Corporation

SunPower 2012

- World-leading solar conversion efficiency
- >2.5 GW solar PV deployed
- Diversified portfolio: roofs to power plants
- More than 200 patents
- 6,000+ employees
- Strategic investment by Total: #11, F500



© 2012 SunPower Corporation

Example “Utility Scale” Power Plants



Greater Sandhill, Mosca, Colorado
19 MW SunPower T20 Tracker



California Valley Solar Ranch, San
Luis Obispo County, 250 MW
SunPower Oasis T0 Tracker



Apple, Maiden NC Data Center
20 MW SunPower T0 Tracker



Montalto Di Castro, Lazio, Italy
84 MW SunPower T0 Tracker



Exelon City Solar, Chicago, Illinois
10 MW SunPower T0 Tracker



DeSoto, Arcadia, Florida
25 MW SunPower T0 Tracker
© 2012 SunPower Corporation

Highly Distributed PV

- 15% technical “limit” or cap is a myth.
- Interconnection study may be triggered -- can be a market barrier.
- California recently reformed Rule 21 to address
- FERC considering whether to follow suit
- Reactive power control can significantly improve “hosting capacity” of the distribution system
- Limited curtailment also an option
- Storage not typically an economic solution




Figure 4. Maximum hosting capacity of the investigated low-voltage network for photovoltaic capacity.

Is the distribution grid ready to accept large-scale photovoltaic deployment? State of the art, progress, and future prospects


Martin Braun^{1,2*}, Thomas Stetz², Roland Bründlinger³, Christoph Mayr³, Kazuhiko Ogimoto⁴, Hiroyuki Hatta⁵, Hiromu Kobayashi⁶, Ben Kroposki⁶, Barry Mather⁶, Michael Coddington⁶, Kevin Lynn⁷, Giorgio Graditi⁸, Achim Woyte⁹ and Iain MacGill¹⁰

© 2012 SunPower Corporation

What About Over Short Distances?

Case Study: Los Vegas Valley Water District

Six Distributed Sites. Minimum Distance: Grand Canyon – Ft. Apache = 1 km




Top – Grand Canyon

Bottom - Ronzone

© 2012 SunPower Corporation
© 2011 SunPower Corporation

Single Site – Highly Variable Day




One minute data
(Ft. Apache)

Partly cloudy day,
highly variable
conditions.


© 2012 SunPower Corporation
© 2011 SunPower Corporation

6 Sites, 1-10 km apart (same day)




© 2012 SunPower Corporation
© 2011 SunPower Corporation

Why? 1-Minute Changes Are Uncorrelated



More Examples of Diversity Over Short Distances



Analysis by Clean Power Research based on 25 node irradiance sensor network on 4 km² footprint (Napa CA), high variability day

Analysis of 1-minute deltas on high variability days from 3 operating mid-size plants (10 MW – 25 MW) in desert, tropical, and midwestern climates

- Consistently, **correlations of 1-minute deltas approach zero at ~1 km (+/- 500 m?).**
- **Zero-correlation distance for 1-second deltas could be as small as 20 meters.**
- **Geographical diversity likely mitigates voltage impacts on distribution systems.**


© 2011 SunPower Corporation

High Penetration In Germany – 28,000 MW DG

Germany Today:

- *Distributed:* 1.1 million systems, 85% rooftop
- *Concentrated:* ~70% in S. Germany
- Penetration exceeding 100% of feeder minimum load is fairly common

Ratio of Installed PV Capacity over
Average Annual Load [MWp/MW]




Average Ratio:
0,34 MWp/MW

~10% of the DSOs:
Ratio > 1 MWp/MW

8 DSOs:
Ratio 2-3 MWp/MW

7 DSOs:
Ratio 3-4 MWp/MW




Source: Y.-M. Saint-Drenan 2010 (IWES)

Sources: Braun 2010, IEA PVPS Task 14 Workshop, 2012 SEPA Germany Fact Finding Report

© 2012 SunPower Corporation
© 2011 SunPower Corporation

Reactive Power Support Key?

Significant Costs Reduction Potential for PV deployment
(exemplary German low voltage grid)




Source: T. Stetz, M. Braun (IWES) 2011

© 2012 SunPower Corporation

Germany – Communications & Monitoring

Example: Operation of SMA “Power Reducer Box” For 100+ kW Systems



- Communication from utility to PV system is unidirectional via ripple control.
- Enables real and reactive power control in conjunction with local autonomous droop functions.
- Monitoring is typically provided, but to PV system owner / operator, not directly to utility; monitoring is via public broadband.
- Transmission system operators contract for PV output estimates and forecasts provided by 3rd parties. Forecasts are based on modeling aggregate regional PV output. Achieving 4-5% RMSE in practice.
- Demonstrates that deterministic, 2-way communication to endpoints (i.e. “smart grid”) is not the only, or necessarily the best option to manage DG.

Courtesy of SMA

SunPower Grid Integration


SunPower offers sophisticated PV control options:

- Automatic Voltage Regulation
- Power Factor Control
- Active Curtailment
- Droop Response
- Dynamic Voltage Control (AVR)

Primarily apply to utility-scale and wholesale DG


Some features can be implemented “behind the meter”

Reactive Power Control / Voltage Regulation



© 2012 SunPower Corporation

Active Power Management Capability



Green = Net Power Flow, Cyan = Backfeed limit setpoint, Yellow = Inverter curtailment %.

© 2012 SunPower Corporation

Summary

- Geographical diversity needs to be accounted for when assessing distribution system impacts, especially over small timescales (e.g. <10 minutes)
- Advanced inverters & plant controls provide control options
- Communications, control strategies must be considered carefully; need not be directly linked
- Thorny issues tend to be cost related – tempting to over specify functionality
- Rule 21 / SGIP reform an important first step, if only to create a more transparent interconnection process

THE WORLD'S STANDARD FOR SOLAR™

Highest Efficiency | Highest Reliability | Guaranteed Performance